



**Bid 008-16**  
**Addendum #1**  
**Questions and Answers**

**PLOW (do you require):**

1. Screw jack adjustable running gear with cast “mushroom style” shoes **YES**
2. Rubber snow deflector on moldboard **YES**
3. Curb guards **YES**
- 4.. Plow markers/blade guide **YES**
5. Rubber cutting edge or Carbide cutting edge **BOTH**
6. 12V electric power unit: vertical mount or horizontal mount **VERTICAL**

**Plow Hitch (please clarify):**

1. Type of mount: Bumper-to-frame or Bumper-to-axle  
If bumper to frame do you need our frame mounting kit **YES**  
  
If bumper to axle do you need the chain block
2. Type of coupler/connection: Pin hitch/pin-ear (center spacing 21” or 31”), drop-pin (QCP), quick hitch, Hustings, etc.
3. 3” or 4” double acting lift cylinder for bumper to frame hitch **YES**  
3” single acton or double acting lift cylinder for bumper to axle hitch  
Do you need chain springs **YES**  
For Installation on Ford F-750, please advise

**TRUCK:**

1. GVW and front axle rating
2. Does the truck have central hydraulics (for the plow) **YES TRUCK HAS HOPPER SPREADER MUST WORK TOGETHER**
3. Is the grill **stationary** or tilting (Need to confirm for the proper hitch configuration)
4. Does the truck have front frame extensions
5. Do you need plow lights mounted on the hood **LIGHTS MOUNTED TO PLOW NOT TO TRUCK**